

# COIL TUBING PRODUCTS

## GPS Pulling Tool - 890 Series

The Coil Solutions GS Pulling Tool is designed to latch standard internal GS profiles such as locks, disconnects and various other completion tools.

The latching mechanism is a robust dog/core design which releases positively from the internal fish neck when a hydraulic differential is applied to the tool. The tool does not require shear pins or drop balls since the differential required to activate the tool is provided by circulating through a choke insert in the core.

- Flow through design
- N2/ fluid compatible
- Can be used with extended reach tools and jars
- Removal of debris in GS profile while engaging
- Designed with high tensile steel



\*Note. All values are rated for STD material.

Tool OD (in)	1.5 GS	2 GS	2.5 GS	3 GS
Connections	1" AMMT	1" AMMT	1 1/2" AMMT	2 3/8" PAC
Tensile Strength (lbs)	25,000	36,000	69,000	120,000
Choke ID (in)	1/8	1/8	1/4	1/4
Length (in)	16	17.3	16	18
Working Pressure (psi)	7000	7000	10,000	10,000

\*Other sizes and thread variations upon request.

**For Further Information Please Contact:**

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada [www.coilsolutions.com](http://www.coilsolutions.com)